

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
24 February 2005 (24.02.2005)

PCT

(10) International Publication Number  
**WO 2005/017518 A1**

(51) International Patent Classification?: G01N 27/49

[GB/GB]: 2a Bridge Street, Wickham, Fareham, Hampshire PO17 5JF (GB).

(21) International Application Number:  
PCT/GB2004/003454

(74) Agent: BROOKS, Nigel: Hill Hampton, East Meon, Petersfield, Hampshire GU32 1QN (GB).

(22) International Filing Date: 12 August 2004 (12.08.2004)

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SI, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0319043.6 13 August 2003 (13.08.2003) GB

(71) Applicant (for all designated States except US): AN-GLO EUROPEAN DESIGN ENGINEERS LIMITED  
[GB/GB]: 2a Bridge Street, Wickham, Fareham, Hampshire PO17 5JF (GB).


(72) Inventor: and

(75) Inventor/Applicant (for US only): COLLINS, Graham

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: GAS SENSOR



(57) Abstract: A current collector wire (1) is over-moulded with a seal (2) made from a thermoplastic elastomer (Santoprene 64) having a (64) Shore A hardness rating. In a three electrode carbon monoxide sensor three current collector wire (1a, 1b, 1c) and seal (2a, 2b, 2c) combinations are inserted into the body (3) through receiving apertures (12a, 12b, 12c) in a side wall of the body, so that the current collectors protrude through connection apertures (12a, 12b and 12c). The outside diameters of the seals and the bores of the apertures are dimensioned to provide an interference fit of the one in the other. The seals are pressed home into receiving apertures in the body (3) to provide compression of the seals against both current collectors and the aperture bores resultant from the interference. Gold-plated phosphor bronze clips (8) are attached which locate on and are retained by barbs on the housing, thereby trapping the current collector wires and providing electrical contact to external circuitry.

WO 2005/017518 A1